

[www.SherWrite.com](http://www.SherWrite.com)



Submittal Documents Sherwrite  
Tackable Board


# TACKABLE WALLCOVERING

[www.sherwrite.com](http://www.sherwrite.com)

**Class A • ECO FRIENDLY • LIGHT WEIGHT & FLEXIBLE**

## FEATURES & BENEFITS


- 100% Polyester
- 60% Post Consumer Content
- Solid Color Through & Through
- Formaldehyde-Free
- Non-Toxic
- Non-Allergenic
- Installs with LOCTITE® Express Power Grab Adhesive
- No Linoleum Content
- High Impact Resistance
- Odor and Dust Free
- Seams Excellently
- Cuts Cleanly
- No Build Up of Static Electricity
- 10 Year Limited Warranty
- Perfect Solution for Healthcare, Education, Hospitality and Corporate Installations



**SW2402**



**SW4402**



**SW6402**



**SW8402**



**SW0502**



**SW2502**



**SW0602**



**SW4502**



**SW6502**



**SW8502**

# TACKABLE WALLCOVERING

## SPECIFICATIONS

### EASY TO INSTALL

Easily installs using LOCTITE® Express Power Grab Adhesive. It is light weight and ultra-durable, making it easier to handle than the standard linoleum tack surfaces. As always, inspect material carefully BEFORE CUTTING to confirm that the correct color and quantity have been supplied. For detailed installation instructions go to [www.exh-1.com](http://www.exh-1.com)

### WARRANTY

Covered by our industry leading 10-year warranty. This warrants material will be free from any defects in material or workmanship and will meet the design criteria noted in our specifications when properly applied per our recommended installation instructions.

### ACCESSORIES

Available with an aluminum perimeter trim to protect all exposed edges, providing a clean and aesthetically pleasing appearance.

## PHYSICAL PROPERTIES

### COMPOSITION

100% Polyester  
60% Post Consumer Content  
Solid Color Through & Through

### FIRE RATING

Class A  
ASTM-E-84

### WEIGHT

4.90 oz / Sq Ft.

### THICKNESS

.350"  
(9 mm)

### SHEET SIZE

48" x 96"  
(1220 mm x 2440 mm)

### COLORS

10

**Product Guide Specification**  
**SECTION 10 11 00**  
**VISUAL DISPLAY UNITS**  
**SHERWRITE TACKABLE POLYESTER BOARD**

**PART 1 GENERAL**

**1.1 SUMMARY**

- A. Section Includes
  - 1. Sherwrite Tackable Polyester Board
  - 2. Accessories
- B. Related Divisions
  - 1. Division 10 11 00 Visual Display Surfaces: Tackboards

**1.2 REFERENCE STANDARDS**

- A. Provide material that meets the classification ratings below:  
Standard Test Method for Surface Burning Characteristics of Building Materials  
ASTM E-84 Class A.

**1.3 SUBMITTALS**

- A. Product specifications and installation instructions for Sherwrite TACKABLE polyester board.
- B. Product's recommended maintenance for Sherwrite TACKABLE polyester board.
- C. Product Data: Submit manufacturer's product data, including surface preparation and installation instructions.
- D. Samples: Memo size samples (5.50" x 5.50") of the Sherwrite TACKABLE color specified.
- E. Manufacturer's Certification: Submit manufacturer's certification that materials comply with specified requirements and are suitable for intended application.
- F. Cleaning Instructions: Submit manufacturer's cleaning instructions.
- G. Warranty Documentation: Submit manufacturer's standard warranty.

**1.4 QUALITY ASSURANCE**

- A. Manufacturer's Qualifications:
  - 1. Manufacturer regularly engaged, for past 5 years, in manufacture of Dry Erase and Tackable Surface Materials.
- B. Installer's Qualifications:
  - 1. Installer regularly engaged, for past 3 years, in installation of commercial wallcovering and polyester board.
  - 2. Employ persons trained for installation of commercial wallcoverings and polyester board.

C. Composition:

1. Tackable: .370" thick x 48" wide x 96" Long Polyester Board designed for use as a tack surface. 60% Post-Consumer content. Color through and through the board thickness. Formaldehyde-Free, Non-Toxic with high impact resistance.

D. Surface Burning Characteristics: Provide materials that meet a Class I / A rating when tested in accordance with ASTM E-84 for flame spread and smoke developed.

E. Field Samples: Prepare field samples for architect's review and establish requirements for seaming and finish trim.

1. Install sample panel of each Sherwrite TACKABLE item specified in an area designated by the architect.
2. Maintain the approved samples to serve as a standard of performance for the project.

## 1.5 DELIVERY, STORAGE, AND HANDLING

A. Delivery and Acceptance Requirements: Deliver materials to site in manufacturer's original, unopened containers and packaging, with labels clearly identifying product name and manufacturer.

B. Storage and Handling Requirements:

1. Store and handle materials in accordance with manufacturer's instructions.
2. Keep materials in manufacturer's original, unopened containers and packaging until installation.
3. Store materials in clean, dry area indoors, out of direct sunlight.
4. Keep wall coverings clean and dry.
5. Store materials at normal occupied building temperature and humidity for a minimum of 3 days before installation.
6. Do not install TACKABLE polyester board until permanent lighting is in place.

## 1.6 AMBIENT CONDITIONS

A. Rooms to Receive Sherwrite TACKABLE Polyester Board: Weather tight with HVAC settings, including pressure, temperature, and relative humidity, the same as those of occupied building for 3 days before installation, throughout installation, and for 3 days after installation.

## 1.7 WARRANTY

- A. Submit manufacturer's limited ten year Warranty against manufacturing defects.

## PART 2 PRODUCTS

### 2.1 MANUFACTURER

- A. Ventress Inc 118 Renaissance Circle Mauldin SC, info@ventressinc.com.

### 2.2 MATERIALS

- A. Sherwrite Tackable: .370" thick x 48" wide x 96" Long Polyester Board designed for use as a tack surface. 60% Post-Consumer content. Color through and through the board thickness. Formaldehyde-Free, Non-Toxic with high impact resistance.

### 2.3 ACCESSORIES

- A. Aluminum J-Trim for Sherwrite TACKABLE. Clear Satin Anodized aluminum,.370" opening.

## PART 3 EXECUTION

### 3.1 EXAMINATION

- A. Examine surfaces to receive Sherwrite TACKABLE.
- B. Notify architect of conditions that would adversely affect installation or subsequent use.
- C. Do not begin surface preparation or installation until unacceptable conditions are corrected.

### 3.2 SURFACE PREPARATION

- A. Ensure walls are structurally sound, smooth, clean, and dry. Recess nails and screws. Repair irregular tape joints, and remove dust.
- B. Remove mold, mildew, dirt, oil, grease, stains, and marks.
- C. Repair any wall irregularities.
- D. Wall surfaces must be sealed with a quality commercial primer prior to installation of Sherwrite TACKABLE.
- E. Test for and eliminate sources of moisture accumulation into wall or wall cavity. DO NOT INSTALL If moisture content is greater than 5%.
- F. Remove existing wall coverings, including remaining adhesive.
- G. Permanent lighting should be installed and operational.
- H. Beginning of installation means acceptance of surface conditions.

### 3.4 APPLICATION

- A. Install Sherwrite TACKABLE in accordance with manufacturer's instructions, included in each shipment of material.
- B. Acclimate material in the area of installation a minimum of 24 hours before installation.
- C. Examine all materials for color, quantity and quality as specified for the correct location prior to cutting.
- D. Stop installation of material that is questionable in appearance and notify the manufacturer's representative for an inspection.

### 3.4 CLEANING

- A. Follow manufacturer's cleaning instructions for cleaning material soiled during installation. Replace material that cannot be cleaned to "like new" condition.
- B. Do not use harsh cleaning materials, solvents, steel wool, abrasive cleaners or methods that could damage the Sherwrite TACKABLE material.

### 3.5 PROTECTION

- A. Protect installed Sherwrite TACKABLE prior to and after installation.

## TACKABLE WALLCOVERING TECHNICAL DATA SHEET

Composition:	100% Polyester
Weight:	4.90 oz / Sq Ft
Sheet Size:	48" x 96" (1220 mm x 2440 mm)
Thickness:	.350" (9 mm)
NRC:	.30 (Type A Mounting)
Flammability:	Class A (ASTM-E84)

### Properties

- 60% Post Consumer Content
- Solid Color Through & Through
- Formaldehyde-Free
- Non-Toxic
- Non-Allergenic
- Installs with Standard Wallcovering Adhesive
- No Linoleum Content
- High Impact Resistance
- Odor and Dust-Free
- Seams Excellently
- Cuts Cleanly
- No Buildup of Static Electricity
- 10 year Limited Warranty

**SHERWRITE TACKABLE WALLCOVERING  
TECHNICAL DATA SHEET (continued)**



## CARE & MAINTENANCE

### RECOMMENDED CLEANING SOLUTION

- 3% hydrogen peroxide mixed with distilled water (stain removal only).

### CLEANING INSTRUCTIONS

- Fresh spills should be blotted as soon as possible. This prevents the polyester from absorbing the spill.
- A plastic bristle brush can be used if there is any surface dirt or deposit. Do not aggressively brush the area as you can change the appearance of the polyester board.
- Thoroughly vacuum the area to remove any loose impediments. Use a soft brush attachment.
- Using the appropriate cleaning solution from the above recommendations, spray the solution onto a clean white cloth. Do not oversoak.
- Use the cloth to blot the stain gently, starting from the outside of the stained area and moving inward.
- If the cleaning cloth starts to dry, add more solution to a fresh cloth and repeat until the stain is removed.
- When finished, remove any remaining cleaning solution from the polyester board with a fresh, dry cloth.
- Remove any residue with a clean cloth or sponge soaked in water.

The TACKABLE Polyester Board should now be clean. Allow the area to air dry thoroughly.

## SHERWRITE TACKABLE WALLCOVERING INSTALLATION INSTRUCTIONS

**Preparation of goods:** Examine material to assure that quantity, color and quality are as ordered.

**Preparation of Substrate:** TACKABLE can be installed over almost any properly prepared surface. Surfaces to be covered must be clean, smooth, dry, uniform in color, and structurally sound. Loose paint or wallcovering must be removed.

**Direct Adhesion:** Be certain that the wall surface will hold an adequate bond using the recommended LOCTITE Adhesive. If there is any doubt about the surface over which the material is to be installed, we strongly suggest installing a mock up to insure a proper bond.

Pre-fit all panels to be installed, trimming where required. Once all of the panels have been properly fitted, begin installation by applying ONLY with LOCTITE Express Power Grab Construction Adhesive to the backside of the TACKABLE panels.

Place the LOCTITE Adhesive into a caulking gun, cut the nozzle to produce a ¼" thick bead.

First, apply a bead of adhesive around the entire perimeter of the Tackable panel. The adhesive bead should be no more than 1-2" from the perimeter.

Using a ZIG ZAG pattern, apply adhesive over the remaining interior areas of the panel, keeping each line of adhesive approximately 18" apart. Apply the panel to the prepared surface within 15 minutes after adhesive is applied. **Wait NO LONGER than 15 minutes!**

Using your hand, smooth down the entire surface of the panel to insure consistent contact is made across the full length and width of the Tackable Panel.

**Clean Up:** Be sure to remove all excess adhesive immediately using a natural sponge or soft cloth and a warm, mild soap solution. Do not use abrasive cleaners. Rinse thoroughly with water and dry with clean toweling. Change water frequently.

**Important:** If you have any questions about the material, stop working and notify your supplier. We are not responsible for the appearance and performance of the TACKABLE product that is not applied according to these instructions.

## **SHERWRITE TACKABLE WARRANTY**

Sherwrite warrants that their TACKABLE products will be free from defects in material or workmanship when properly applied and installed per our explicit instructions. The TACKABLE Warranty is for a period of 10 years from the date of purchase.

If in the sole opinion of Sherwrite a product covered under this limited warranty is determined to be defective, Sherwrite will replace it free of charge. The liability of Sherwrite under this warranty is limited to the replacement of the defective product only and does not include any responsibility for other damages, including labor.